SR23MR-3

Powerful, tough, durable and designed with value in mind

Engine model: Yuchai YC6M220Z-T20

Rated power: 162 kW/2200 rpm

Operating weight: 23.0 t

Product features

Designed for value durability and power specifically as a bulk waste management and landfill compactor, the 23.0-ton SR23MR-3 features four-wheel drive, torque converter, power shift transmission, stepless speed regulation and articulated frame. For operator productivity and safety, its dual cab comes standard with air conditioning, heating, air purification devices and even a CD stereo. Powered by a Yuchai YC6M220Z-T20 engine.



VALUE AT WORK

SHANTUI VALUE THAT WORKS

Shantui Construction Machinery Co., Ltd.

ADDRESS:

No. 58, G327 Highway Jining City, Shandong, CHINA

TEL: +86-537-2909369 FAX: +86-537-2311219 EMAIL: trade@shantui.com

SR23MR-3

Technical specifications:

Overall length: 7360 mm Minimum turning radius: 6786 mm

Overall width: 3200 mm Fuel capacity: 400 L

Overall height: 3640 mm


hl	WEIGHT AND DIMENSIONS	Weights	Operating weight	23000 kg		
			Axle load, front	11500 kg		
		Compaction characteristic	Axle load, rear	11500 kg		
			Static linear load, front/rear	626 N/cm		
			Working width	3090 mm		
			Drum diameter	1620 mm		
			Wheelbase	3350 mm		
4	BLADE	Maximum lifting height		1050 mm		
		Maximum cutting depth		160 mm		
		Blade capacity		8.7 m³		
°	ENGINE AND DRIVE TRAIN	Engine	Make & model	Yuchai Y0	Yuchai YC6M220Z-T20	
			Туре	Turbocharged		
			Fuel	Diesel		
			Cooling	Water		
			Number of cylinders	6		
			Rated power	162 kW		
		Drive Train	Rated speed	2200 rpm		
			Minimum ground clearance	455 mm		
			Maximum climbing ability	100%		
			Forward speed	1	0~4.37 km/h	
				II	0~6.82 km/h	
			Reverse speed	III	0~10 km/h	
				1	0~4.37 km/h	
				II	0~6.82 km/h	
				III	-	
T <u>å</u>	CONTROLS	Brakes	Service brake	Pressurized air braking		
		Parking brake		Mechanical		
			Steering system	Oscillatin	Oscillating, articulating	


Steering system
Steering method

Steering angle (Grad)
Oscillating angle (Grad)

OVERALL DIMENSIONS

Steering





Hydrostatic

±36°

±7°

THE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. THE PICTURES MAY INCLUDE OPTIONS. THE ACTUAL COLOR & APPEARANCE OF THE PRODUCT MAY DIFFER FROM WHAT IS SHOWN.